

**BOVA****FALL ARREST
LANYARD**

LANYARD

EXTENSIO RANGE

**CODE: LANY01220****Sizing**
1750mm**Weight**
1.65kg**Max Fall Weight**
140kg**Standards**
SANS 50354 | EN 354
SANS 50355 | EN 355

LANYARD FEATURING:

- Double leg with scaffold hooks
- Single leg with snap hook
- Shock absorber

DESCRIPTION:

This is a double leg, shock absorbing lanyard with two Scaffolding hooks and a single Snap hook connector that is engineered to attach to a dorsal D-Ring on a stand-alone, fall arrest harness.

This lanyard is recommended for those who are required to navigate obstacles whilst working at heights. The double leg lanyard improves safety to the wearer by allowing them to remain attached to at least one anchor point at all times, through the use of one hook, while moving the second hook around the obstacle to a new anchor point.

The built-in shock absorber is engineered to reduce the total force experienced in a fall to a survivable force of less than 6kN.

MATERIALS:

Webbing:

- 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes

Lanyard length:

- 1750mm when intact
- 3450mm when shock absorber is fully deployed

Hooks:

- Corrosion-resistant steel hooks:
 - Scaffolding hooks: 50mm gate opening that can withstand a force of 23kN
 - Snap hook: 20mm gate opening that can withstand a force of 22kN

This product is manufactured in South Africa by BBF Safety Group (Pty) Ltd. in an ISO 9001 accredited factory.

April 2020