



**CLASSIC PROTECTIVE EYEWEAR**  
**DV-55C-AF (CLEAR) & DV-55G-AF (GREY)**



**DV-55C-AF**



**DV-55G-AF**



**Description**

Dromex® CLASSICS polycarbonate dual lens spectacles are designed to protect the user's eyes from flying debris, particles, UV (Ultra Violet, DV-55C-AF model) light and sun glare (DV-55G-AF model) during work activities. Suitable for indoor and outdoor environments (DV-55G-AF), construction, warehouse and general industry applications without compromising worker safety and vision.

Designed for compatibility with other PPE, such as industrial hats, hearing protectors and respiratory protective half mask devices.

The Classic spectacle is lightweight with an anti-scratch, anti-fog and impact resistant polycarbonate lens, adjustable temples and soft rubber nose pad.

These features ensure a firm fit promoting enhanced product performance and user comfort.

**Special Instructions**

- Failure to adhere to all instructions and precautionary measures can result in injury.
- If the user has eye conditions or vision impairment, they must consult with a registered physician prior to use.
- Any damages to this protective eyewear, may reduce clarity of sight that could result in injury.
- Following any major detectible defects on the spectacle, the spectacle should be replaced immediately.
- This protective eyewear is suitable for use to the lowest marking on the lens (ocular) and frame.
- If the lens becomes damaged the spectacle should be replaced.
- This spectacle is designed to be used with other PPE equipment.
- Although the manufacturer has examined this eyewear under the system for ensuring quality of production by means of monitoring and inspection, we recommend that all eyewear should be thoroughly inspected before use to ensure no damage is present.

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The gloves and information contained herein are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. Actual conditions of use cannot be directly simulated in a test environment, therefore it is the responsibility of the user and not the manufacturer or supplier to determine the suitability for intended use.

**Compliance & Conformity**

Complies with CE, EN 166:2001

Quality System as per ISO 9001:2008.

**Specifications**

- Style: Polycarbonate lens with UV protection (clear lens colour) or sun glare protection (grey lens colours) rubber nose pad and adjustable temples
- Lens: Polycarbonate, that is anti-fog and scratch resistant
- Frame: Polycarbonate frame and hard rubber temples
- Refractive Power: ±0.06 D
- Astigmatism: 0.06 D
- Optical class: 1 - ± 0, 06 DIOPTRIS for permanent wear
- Lateral vision: 180 degrees
- Minimum Velocity particles: Class F, 45 m/s
- Mass: 24g
- Additional: Available in clear lens, part number DV-55C-AF and grey lens, part number DV-55G-AF

**Packaging, Storage & Obsolescence**

Packed 12 individually wrapped spectacles in a box and 25 boxes per carton (300 spectacles per carton).



**Inspection Frequency and Details**

Spectacles should be free of any potential contaminants that can affect its intended performance. The spectacles should be inspected by the user at the end of every use and then again prior to each use. Cracked eyewear must be disposed of as they will reduce eye protection and obstruct vision.

**Cleaning & Maintenance**

Designed as re-usable protective eyewear. After use clean with a mild cleaning liquid, carefully rinse off all traces of the cleaning liquid and dry with a soft cloth and gently wipe with a soft spectacle cleaning material. Do not clean on clothing nor use abrasive cleaners.

**Limitations of Use**

These spectacles should not be used for any athletic game, recreational activities, paintball or simulated water activities. These spectacles are not suitable to protect from chemical, biological, radiological, and nuclear (CBRN) agents.

**Recommendations & Restrictions**

The uses of these spectacles are restricted to the scope and applications as intended by EN 166:2001.


**Shelf Life**

The duration of these spectacles cannot be determined as they are intended for normal day to day use. Ensure proper care and maintenance (inspection and cleaning) is adhered to. Under normal circumstances the spectacles should offer adequate protection for 3 years.

**Disposal**

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Safety eyewear should be disposed of considering the hazardous substance they were used for or could be contaminated with. Please consider recycling.

**Materials**



1. Polycarbonate lens (right) (55C – Clear & 55G – Grey).
2. Polycarbonate lens (left) (55C – Clear & 55G – Grey).
3. Black polycarbonate frame.
4. Black polycarbonate frame 3-point adjustable temple right (EN 166-F-CE).
5. Black 3-point adjustable temple left (DroVision/Dromex).
6. Rubber soft nose bridge right.
7. Black rubber soft nose bridge left.
8. Stainless Ø1.2mm x 9mm countersink self-tapping set screw.

**Marking**

| Item | Temple     | Ocular/(s)  |
|------|------------|-------------|
| 55C  | EN166-F-CE | DV2-1.2 1FN |
| 55G  | EN166-F-CE | DV5-2.5 1FN |

**Dromex: Unit 1, 1 Blase Road, New Germany, 3620, South Africa**  
**T. +27(31) 713 1960 E. info@dromex.co.za**  
**www.dromex.co.za**