

## KEY FEATURES

### FFP 2 FILTRATION HALF MASK

- Head Tie Back
- Nose Piece Internal
- Nose piece external
- Meltblown 2 x 25 GSM
- Needlepunch 1 x 160 GSM
- Non-Woven 1X 35 GSM
- Full mask dimension: Length = 135mm
- Width = 135mm Cross Section = 155mm
- Plastic Breathing Valve x 1
- BFE= 95 % or up
- Product Colour: White

## MATERIAL COMPOSITION

- 5 MM flat rope
- Bridge of nose PP white double core double face
- Non-Allergen Sponge for extra comfort
- Needle Punch 160 GSM
- Meltblown 25 GSM
- Non-Woven 35 GSM
- Plastic Breathing Valve



## COUNTRY OF ORIGIN

- SOUTH AFRICA

## INTENDED USAGE

The need for the mask to be use depends on the contaminants. The user will recognize when to change by smell, taste and difficulty in breathing or by irritation to the respiratory tracts.

The ambient air must contain at least 17% oxygen by volume.

Face mask do not provide protection against gases vapors and fumes.

## DO NOT USE FOR

Do not use in explosive atmospheres.

Do not use for firefighting.

## APPROVALS AND STANDARDS

- ✓ SAHPRA
- ✓ NRCS
- ✓ ARMSCOR
- ✓ SABS



## SHELF LIFE AND STORAGE

- Batch tested done on site.
- Store masks in the original packaging, away from contaminated areas, dust, sunlight, extreme temperatures, excessive moisture, and damaging chemicals.
- Store in temperatures between -20 °C and +30°C and not exceeding 80% humidity.

## TIME USE LIMITATION

- Replace the mask when it becomes dirty, damaged, or difficult to breathe through.

## WARNINGS

- The high protection masks are not intended for reuse and shall be discarded after each procedure. Check your masks production date.
- Always follow the instructions for use to ensure mask is properly sealed.
- Not recommended for children under 3.

## MASK/BOX

20